

## 深圳市万利兴科电子有限公司 SHENZHEN MANLY BATTERY CO.,LTD

# **Lithium Iron Phosphate Battery**

# 12.8V 300Ah

### Feature:

- Ultra-long life, the service life can reach 10-15 years.
- The battery pack can be charged at any time, discharged at any time, and requires no maintenance.
- The battery has excellent safety performance, and there are no safety hazards such as fire and explosion.
- With battery management system, it has protections such as overcharge, over-discharge, over-current, over-temperature and short circuit
- Does not contain any pollutants, green and environmentally friendly batteries.

### Applications:


- UPS
- Boat
- Lighting
- Wind/Solar energy
- Communication base station

### Parameter table:

Farameter table.		
Characteristics	Parameter	Condition
Rated voltage	12.8V	
Rated Capacity	300Ah	@0.2C₅A discharge
Maximum charging voltage	14.6V	CC/CV
Standard charging current	60A	
Maximum charging current	100A	
Standard discharge current	60A	
Maximum discharge current	150A	
Discharge cut-off voltage	10V	@0.2C₅A discharge
Charging temperature	<b>0 ~ 45℃</b>	
Discharge temperature	-10 ~ +60 ℃	
Storage temperature	<b>-20 ~ +45</b> ℃	≪1 month
	<b>-20 ~ +25</b> ℃	3 ~ 12 months
	<b>25℃</b>	>12 months
Cycle life	≥5,000	
Waterproof level	IP65	
Communication protocol	1	
Output method	M8	
Packing	ABS plastic shell	
Weight	Approx:34.2kg	Subject to the actual
Size	520*268*220*240mm(L*W*H*T)	±3mm



For reference only, the actual product shall prevail.




**Dimensional diagram** 




### 深圳市万利兴科电子有限公司 SHENZHEN MANLY BATTERY CO., LTD


## **Lithium Iron Phosphate Battery**


### Curve graph:




### Different Temperature Discharge Curve @0.5C,25℃







### Charge Characteristics @0.2C&0.5C, 25℃



#### **Open Circuit Voltage VS. SOC%** 13.6 13.4 Open Circuit Voltage(V) 13.2 13.0 12.8 12.6 12.4 12.2 12.0 0% 20% 40% 60% 80% 100% SOC(%)

### Web: www.manlybattery.com